

Fitting Instructions for the Door Surround and Shallow Georgian

Step 1

(A) Measure inside width of Door Surrounds and, using a suitable pencil/marker, mark vertically onto the wall.

(B) Mark line for desired position of underside of Canopy. Ensure all markings are level & plumb (spirit level)

Step 2

(C) Fix, using 100mm Concrete fixings at max 600mm c/c, treated batten timbers (vertically) 2no onto the wall inside markings and 2no flush with the door reveal.

Step 3

(D) Mark centre-line on canopy soffit.

(E) 1st operative to offer soffit to wall marrying up all marks.

Step 4

(F) 2nd operative to drill 6.5x120mm tight to both ends (central) Fix using 7.5x100mm concrete fixing with oversize mudguard washer.

Step 5

(G) Once canopy all level, put fixings adjacent to all baffles and at both ends of canopy.

(H) Use spirit level to double check (loosen & pack if necessary)

Step 6

(I) Mark and pre-drill roof of canopy along back flange at max 600mm centres, using 6.5mm drill bit. Holes to be equally spaced and at same height.

(J) Offer roof to soffit - roof lip to overlap with soffit lip edges. Drill (6.5x120mm bit) through pre-drilled holes into brickwork. Fix using 7.5x100mm concrete fixing with washers to receive colour match caps.

Step 7

(K) Place Door Surround onto the timber battens. Double-check level & plumb using spirit-level, or follow the line of the brick-course / door frame.

(L) Fix through sides of the Surrounds, into the battens, using 50mm wood screws with washers (for colour matching caps)

Step 8

(M) Silicone mastic around the door surrounds & canopy to the wall and door frame using appropriate colour(s).

(N) Cover visible screw heads/washers with correct colour caps.



Tel: 01536 446393 **Email:** sales@thecanopyshop.co.uk **Web:** www.thecanopyshop.co.uk

6 Canberra House, Corbygate Business Park, Corby, NN17 5JG